

**Power With Value****POWER BY PERKINS ENGINE GENERATOR SETS****MAIN SPECIFICATIONS OF GENERATOR SETS(50HZ)**

Generator Set Model	Continuous output		Standby output		Perkins Engine Model	Fuel consumption (g/kw.h)	No. of cylinder	Displacement (L)	Alternator model	Dimension (LxWxH) mm	N.W (kg)	Fuel tank capacity (L)
	KW	KVA	KW	KVA								
PE7&PE7/S	7	9	8	10	403D-11G	252	3	1.131	SLG164B	1580x810x930	359	50
PE10&PE10/S	10	13	11	14	403G-15G	264	3	1.496	SLG164C	1580x810x930	450	100
PE16&PE16/S	16	20	18	22	404D-22G	243	4	2.216	SLG184E	1580x810x990	467	100
PE24&PE24/S	24	30	26	33	1103A-33G	210	3	3.3	SLG184G	1580x810x1165	667	100
PE36&PE36/S	36	45	40	50	1103A-33TG1	212	3	3.3	SLG224D	1595x810x1150	730	100
PE48&PE48/S	48	60	52.8	66	1103A-33TG2	211	3	3.3	SLG224E	1580x810x1165	780	100
PE52&PE52/S	52	65	57	71.5	1104A-44TG1	207	4	4.4	SLG224F	1760x810x1165	800	150
PE64&PE64/S	64	80	70	88	1104A-44TG2	213	4	4.4	SLG224G	1760x810x1165	820	200
PE80&PE80/S	80	100	88	110	1104C-44TAG2	226	4	4.4	SLG274C	2240x960x1315	905	200
PE108&PE108/S	108	135	118	148	1006TAG	205	6	5.99	SLG274E	2240x960x1315	1099	300
PE120&PE120/S	120	150	132	165	1006TAG2	206	6	5.99	SLG274F	2240x960x1315	1110	400
PE140&PE140/S	140	175	154	192	1106C-E66TAG4	206	6	6.6	SLG274G	2345x810x1365	1300	400
PE200&PE200/S	200	250	220	275	1306C-E87TAG6	223	6	8.7	SLG274K	2430x960x1590	2170	600
PE280&PE280/S	280	350	308	385	2206C-E13TAG2	218	6	14.6	SLG314F	3280x1130x1950	3300	700
PE320&PE320/S	320	400	352	440	2206C-E13TAG3	201	6	14.6	SLG314G	3280x1130x1950	3400	800
PE360&PE360/S	360	450	396	495	2506A-E15TAG1	216	6	15.8	SLG354C	3420x1120x1900	3800	1000
PE400&PE400/S	400	500	440	550	2506A-E15TAG2	211	6	15.8	SLG354D	3420x1120x1900	3840	1000
PE480&PE480/S	480	600	528	660	2806A-E18TAG1	203	6	18.13	SLG354E	3380x1500x2100	3940	1000
PE520&PE520/S	520	650	572	715	2806A-E18TAG2	203	6	18.13	SLG354F	3380x1500x2100	4706	1000
PE584&PE584/S	584	730	642	800	4006-23TAG2A	209	6	22.92	SLG404A	3770x1700x2130	4750	1200
PE640&PE640/S	640	800	704	880	4006-23TAG3A	209	6	22.92	SLG404G	3770x1700x2130	4800	1200
PE720&PE720/S	720	900	792	990	4008TAG1A	206	8	30.561	SLG404H	4760x1995x2330	7590	1200
PE800&PE800/S	800	1000	880	1100	4008TAG2A	208	8	30.561	SLG404J	4760x1995x2330	7611	1500
PE1000&PE1000/S	1000	1250	1100	1375	4012-46TWG2A	212	12	45.8	SLG454A	4900x1860x2350	9154	1500
PE1200&PE1200/S	1200	1500	1320	1650	4012-46TAG2A	209	12	45.8	SLG454C	4805x2180x2350	11580	1500
PE1460&PE1460/S	1460	1825	1606	2008	4016TAG1A	205	16	61.1	SLG454E	6000x2775x3660	15500	1500
PE1600&PE1600/S	1600	2000	1760	2200	4016TAG2A	209	16	61.1	SLG454F	6000x2775x3660	15500	1500
PE1760&PE1760/S	1760	2200	1936	2420	4016-61TRG3	209	16	61.1	SLG454G	6000x2775x3660	15800	1500



Power With Value

POWER BY PERKINS ENGINE GENERATOR SETS

MAIN SPECIFICATIONS OF GENERATOR SETS(60HZ)

Generator Set Model	Continuous output		Standby output		Perkins Engine Model	Fuel consumption (g/kw.h)	No. of cylinder	Displacement (L)	Alternator model	Dimension (LxWxH) mm	N.W (kg)	Fuel tank capacity (L)
	KW	KVA	KW	KVA								
PE9-6&PE9-6/S	9	11.3	9.9	12.5	403D-11G	252	3	1.131	SLG164A	1580x810x930	359	50
PE13-6&PE13-6/S	13	16	14	18	403D-15G	264	3	1.496	SLG164C	1580x810x930	450	100
PE20-6&PE20-6/S	20	25	22	27.5	404D-22G	243	4	2.216	SLG184E	1580x810x990	467	100
PE28-6&PE28-6/S	28	35	31	38.5	404D-22TAG	210	4	2.216	SLG184F	1580x810x990	550	100
PE50-6&PE50-6/S	50	62.5	55	68.7	1104D-44TG1	207	4	4.4	SLG224D	1760x810x1165	800	150
PE55-6&PE55-6/S	55	68	60	75	1104D-E44TG1	207	4	4.4	SLG224E	1760x810x1165	820	150
PE74-6&PE74-6/S	74	92.5	81	102	1104A-44TG2	213	4	4.4	SLG224G	1760x810x1165	850	200
PE91-6&PE91-6/S	91	114	100	125	1104C-44TAG2	226	4	4.4	SLG274C	2240x960x1315	905	200
PE120-6&PE120-6/S	120	150	132	165	1006TAG	205	6	5.99	SLG274E	2240x960x1315	1099	300
PE135-6&PE135-6/S	135	168	148	186	1106D-E66TAG3	206	6	6.6	SLG274E	2345x810x1365	1250	400
PE160-6&PE160-6/S	160	200	176	220	1106D-E66TAG4	206	6	6.6	SLG274G	2345x810x1365	1300	400
PE185-6&PE185-6/S	185	231	204	254	1306C-E87TAG3	213	6	8.7	SLG274H	2430x960x1590	1990	600
PE196-6&PE196-6/S	196	245	216	270	1306C-E87TAG4	213	6	8.7	SLG274H	2430x960x1590	2000	600
PE315-6&PE315-6/S	315	400	346	440	2206D-E13TAG2	198	6	14.6	SLG314E	3280x1130x1950	3300	700
PE350-6&PE350-6/S	350	438	385	481	2206D-E13TAG3	201	6	14.6	SLG314F	3280x1130x1950	3400	800
PE400-6&PE400-6/S	400	500	440	550	2506D-E15TAG1	216	6	15.8	SLG354C	3420x1120x1900	3800	1000
PE456-6&PE456-6/S	456	570	502	627	2506C-E15TAG3	211	6	15.8	SLG354D	3420x1120x1900	3840	1000
PE550-6&PE550-6/S	550	687	605	756	2506C-E15TAG4	211	6	15.8	SLG354E	3420x1120x1900	3900	1000